



## Industrial-Grade Media Converter

### GNT-G122SAB-H

Transmission Range: 20KMTransmission Rate: 1000Mbps

■ Power Inout: DC5V1A


#### **Product Features**

- Adapter Power Supply
- Aluminium Alloy Abrasive Material
- Convenient

## **Product Figure**



### Dimension (mm)



## Installation Diagram





# Specifications

	ONT O LOOP LI
Model	GNT-G122SAB-H
Protocol Standard	IEEE802.3u/z/ab
Network Interface	RJ45 10/100/1000Mbps Self-Adaption
	Transmission Distance:100m
Fiber Interface	Single Mode SC
	Optical Fiber Type:Single Mode 9/125µm
	1310T/1550R (A) / 1550T/1310R (B)
	Transmission Rate:1000Mbps
	Transmission Distance:≤20KM
Performance & Specification	Forwarding Mode:Store Forward
	Transfer Mode:Full Duplex/Full Duplex Automatic Connection
	Network Latency:≤150µs
Power	Power Type:External Power
	Power Input:AC100V~240V 50/60Hz
	Power Inout:DC5V1A
	DC Socket:2.5x5.0mm
Physical Specifications	Size:95*70*25mm, Weight: 0.43KG
Working Environment	Operating Temperature: -40°C~75°C
	Storage Temperature: -10°C~55°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE Mark
	FCC Part15,Class B
	RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	AC Power Cable,User Manual