

Gigabit SFP Module Rack

GNT-G1618FG

- Total 30W Power
- 6 ports RJ45
- 12ports SFP

Product Features

- Support AC 90V~240V or PoE Powered(LAN 1)
- 6KV Lightning & 8KV ESD Protection
- Low power consumption 30W
- Metal body for quickly dissipate heat


Product Figure



Dimension (mm)



Installation Diagram



Specifications

Model	GNT-G1618FG
Ports	(1GE+2SFP)*6Group
Bandwidth	36Gbps
Packet Forwarding Rate	26.784Mbps
Transmission Distance RJ45 Port	100m
Transmission Distance SFP Port	Depends on the transmission distance of the optical module
SFP Ports	SC
SFP Ports	1000Base-X; 100Base-X
Power Input	AC 90V-240V, 50~60Hz, PoE Powered (LAN 1)
Total Power	30W
Working Temperature	-30°C~60°C
Storage Temperature	40°C~70°C
Storage Humidity	5%~90% Non-condensing
Lightning Protection	6KV
ESD Protection	8KV
Operating Humidity	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Transmission Rate	Network: 1000Mbps (Full Duplex); SFP: 1000Mbps
Size	430*180*45mm
Weight	1.43KG
Certification	CE
	FCC
	RoHS 2.0
Warranty	Whole Device: 1Year
Package Content	Devices; User Manual; Earing Rack(19-inch cabinet); SFP Dust plug; Screw