

AI PoE Switch


GNT-ES08ED-P6

- Total 65W Power Supply
- 6 ports PoE
- 2 ports Uplink

Product Features


- AI Watchdog Function
- 6KV Lightning & 8KV ESD Protection
- Support bt 60W High Power

Ports Description




- ① 100Mbps PoE ports
- ② bt 60W Power Port
- ③ 100Mbps Uplink Port

Dimension (mm)



Installation Diagram



Specifications

Model	GNT-ES08ED-P6
Ports	PoE (1-5):10/100Mbps PoE ports (RJ45) PoE (6): 10/100Mbps PoE port (RJ45),Support bt 60W High Power LAN(7-8):10/100Mbps uplink ports (RJ45)
Transmission Rate	10/100Mbps: Full Duplex / Half Duplex
Transmission Distance	130m
Performance Specification	Bandwidth:1.6Gbps
	Network Latency (10 to 100Mbps)c = 16us (use the 64byte package size)
	MAC address table: 2K
	Packet Forwarding Rate: 1.2Mpps
Networking Standard	IEEE 802.31 10BASE-T
	IEEE 802.3u 100BASE-TX
	IEEE 802.3x Flow Control
	IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input: AC 90-240V Total≤65W AI Watchdog: Port 1-6 Power Output: PoE 1-5 Port: 1245+/- 3687-≤30W PoE 6 Port: 1245+/- 3678- ≤60W
Protection Level	Lightning Protection: 6KV ESD Protection: 8KV
Physical Specifications	Size(L"W"H): 190mm*80mm*36mm, Weight: 0.5KG
Working Environment	Operating Temperature: - 30℃-60℃
	Storage Temperature: - 40℃-70℃
	Operating Humidity: 10%-90% Non-condensing
	Storage Humidity: 5%-90% Non-condensing
Certification	CE
	FCC
	RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	AC Power Cable,User Manual