

AI PoE Switch

GNT-ES12ED-P10

- Total 120W Power Supply
- 10 ports PoE
- 2 ports Uplink

Product Features


- AI Watchdog Function
- 6KV Lightning & 8KV ESD Protection
- Support bt 60W High Power

Ports Description




- 1 100Mbps PoE Ports
- 2 bt 60W Power Ports
- 3 100Mbps Uplink Ports

Dimension (mm)



Installation Diagram



Specifications

Model	GNT-ES12ED-P10
Ports	PoE (1~8):10/100Mbps PoE ports (RJ45) PoE (9~10):10/100Mbps PoE ports (RJ45),Support bt 60W High Power LAN(11~12):10/100Mbps uplink ports (RJ45)
Transmission Rate	10/100Mbps: Full Duplex / Half Duplex
Transmission Distance	130m
Performance Specification	Bandwidth:2.4Gbps
	Network Latency (10 to 100Mbps): $\leq 16\mu s$ (use the 64byte package size)
	MAC address table: 2K
	Packet Forwarding Rate: 1.8Mpps
Networking Standard	IEEE 802.3i 10BASE-T
	IEEE 802.3u 100BASE-TX
	IEEE 802.3x Flow Control
	IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input: AC 90~240V Total $\leq 120W$ AI Watchdog: Port 1~10 Power Output: PoE 1~8 Port:1/2(+52V),3/6(GND) $\leq 30W$ PoE 9~10 Port:1245(+52V),3678(GND) Compatible1/2(+52V),3/6(GND) $\leq 60W$
Protection Level	Lightning Protection: 6KV ESD Protection: 8KV
Physical Specifications	Size(L*W*H): 190mm*140mm*43mm, Weight: 1.0KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE
	FCC
	RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	AC Power Cable,User Manual